

## SPECIFICATIONS

<b>Model</b>	<b>W622EAHZ37EA</b>
<b>Camera</b>	
Image Sensor	1/3.08" SC2332H CMOS
Effective Pixels	1936(H)×1096 (V)
Electronic Shutter	AUTO
Min. Illumination	0.01Lux@F1.2 (AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC / HLC	Support
DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Flip, Mirror
<b>Encode</b>	
Embedded Solution	Mstar SSC335
Video Standard	H.264/H.265
Video Resolution	Main Stream: 1080P@25fps/30fps Sub Stream: 640x360/D1/640*480 @25fps/30fps
Video Bitrates	500Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
<b>IR Led</b>	
IR Led	12pcs SMD IR Leds
IR Distance	15-20M
<b>Lens</b>	
Focal length	3.6mm Fixed lens
<b>Optional Function</b>	
POE, Audio, etc.	

## SPECIFICATIONS

<b>Network Services</b>	
Protocol	RTSP/DHCP/NTP/DST/FTP/SMTP
P2P	Yes
Web	IE, Firefox, etc.
Media	CMS, Android, iOS
ONVIF	2.6 compatible
<b>General</b>	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC $\pm$ 10%
Power Consumption	< 5 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH

