

SPECIFICATIONS

Wireless NVR Model

YC-WF9308-265

Operating System

Embedded Linux OS



Video Input	Network Video	Max. 4CH 5MP Camera
	Network video input broadband	70Mbps
Video Output	HDMI output	1ch Resolution: 1024x768,1366x768,1440x900, 1920x1080p, 2K
	VGA output	1ch Resolution: 1024x768,1366x768,1440x900, 1920x1080p
Recording	Record mode	Manual/Schedule/Motion/Alarm
	Playback	By time/Event
	Backup	USB backup, network download
Hard Disk	Type	1*SATA
	Max. Capacity	6 TB
Network	Network port	1 - RJ45 10M/100M
	Wireless	2 - 5Db WIFI antennas x 2 for cameras + 3Db WIFI x1 for router
Smart Detection	Human Detection	Human Detection, Motion Detection
Network Control		UPnP (play&plug)/SMTP (email service)/PPPoE (dial-up) DHCP (Automatically obtain an IP address), etc...
Others	Power Supply	DC12V/2A
	USB	2 - USB 2.0 for mouse and USB drive
	Power Consumption (W)	≤5W (Without HDD)
	Operate Temperature (°C)	-10°C~+55°C
	Working Humidity (%) RH	10%~90%
	Dimension (WxVxH)	257mm × 210mm × 45mm
	Weight (without HDD)	≤1Kg

SPECIFICATIONS

Wireless Camera - Bullet Model

WF933AHZ37FA



Sensor	1/2.7" Progressive Scan Sensor
Signal System	PAL/NTSC
Compression standard	H.265, H.264, H265+
Minimum illumination	Color: 0.01 Lux; 0 Lux with IR on
Shutter	AUTO 1/25s - 1/25,000s
Lens	3.6MM
IR LED	12pcs IR SMD LEDs
IR Distance	15-20 M
OSD	Date Time & Title
White Balance	Auto
Day&Night	Auto / Color / BW
3D-DNR	Auto
Mirror/Flip	On / Off
Audio	Optional
Video Stream	Main Stream: 3MP (2306x1296) @15fps Sub Stream: 640x360 @15fps
Network	RJ45 / WIFI 802.11b/g/n
Working Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Power Input	DC12V-1A
Power consumption	≤6W
Dimension (L x W x H)	205mm × 70mm × 55 mm
Weight	≤1Kg