

## SPECIFICATIONS

<b>Model</b>	<b>W942G-30PTZ-V2</b>
<b>Camera</b>	
Image Sensor	1/2.8" Sony IMX307 CMOS
Effective Pixels	2 megapixels
Electronic Shutter	AUTO
Min. Illumination	0.001Lux@F1.2 (AGC ON)
Day/Night	Auto/Color/(B/W)
System	PAL/NTSC
White Balance	Auto/Indoor/Outdoor
OSD Overlay	Yes
Image Mirror	Yes
Privacy Mask	Yes
<b>Encode</b>	
Video Standard	H.265/H.264
Video Resolution	Main Stream: 18fps@1080P(PAL)/ 20fps@1080P(PAL) Sub Stream: 25/30fps@640x352
Video Bitrates	32Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711/G.726
Audio Input	Built-in Mic
Audio Output	Built-in loudspeaker
IR Led	8pcs array IR Led (4 near + 4 far)
Two-way Audio	Yes
<b>IR Led</b>	
IR Led	6 pcs SMD IR Leds
IR Distance	20-30 M
<b>Lens</b>	
Focal length	2.8-12mm Motorized lens

## SPECIFICATIONS

<b>Network Services</b>	
Protocol	TCP/IP/HTTP/RTSP/FTP/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE, Firefox, Chrome, Edge, Safari, etc. (flash video)
Media	CMS, Android, iOS
ONVIF	2.04 compatible
Alarm Event	Motion Detection, Email Alert, Snapshot FTP, SD Storage
<b>General</b>	
Network Port	1-RJ45, 100Mbps
Wireless	2.4G b/g/n external 3DB antenna
Reset Button	Yes
Power Supply	12 VDC $\pm$ 10%
Power Consumption	< 10 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH