

GROOVED BUTTERFLY VALVE, GEAR OPERATED

FIG. FFA-F1022-300

Specifications

- Meet or exceed the requirements of EN 593 and MSS SP-67 Standard.
- Vulcanized Disc Design for Bubble-Tight Shutoff.
- Outdoor and Indoor rated.
- Flag Type Position Indicator.
- Built-in Supervisory Switch.
- Grooved Ends Dimensions meet AWWA C606 Standard or other IPS Pipe.
- Face to Face Dimension complies with MSS SP-67.
- UL/ULC 1091 Listed, FM 1112 Approved, VdS 2100-08en and 3C Certified.
- Rated Working Pressure:
300 psi for UL/ULC Listed
300 psi for FM Approved
16 bar for VdS and 3C Certified


Corrosion Protection

- Fusion Bonded Epoxy Coated Interior and Exterior to AWWA C550 Standard.

Material Specifications

Part	Material	ASTM Specification
Body	Ductile Iron	A536 Grade 65-45-12
Disc	EPDM fully Encapsulated Ductile Iron	
Shaft	Stainless Steel	A276 Type 431
Bushing	Brass	B124 C37700
Housing	Gray Cast Iron	A126 Class B
Fasteners	Carbon Steel	A307 Grade B

Schematic



Main Dimensions (mm/inch)

Size	A	B	E	F	M	N
2	220/8.70	76/2.99	84/3.30	190/7.48	150/5.90	228/8.98
2.5	230/9.00	85/3.35	97/3.81	190/7.48	150/5.90	228/8.98
3	235/9.25	90/3.55	97/3.81	190/7.48	150/5.90	228/8.98
4	265/10.45	110/4.30	116/4.56	190/7.48	150/5.90	228/8.98
5	285/11.25	120/4.75	148/5.81	215/8.46	157/6.18	235/9.25
6	305/12.00	145/5.70	148/5.81	215/8.46	157/6.18	235/9.25
8	360/14.25	180/7.00	133/5.25	280/11.02	205/8.07	310/12.20
10	410/16.20	230/9.00	159/6.25	280/11.02	230/9.06	333/13.11
12	435/17.13	260/10.25	165/6.50	280/11.02	230/9.06	333/13.11