




Sprinklers

PRODUCT CATALOGUE

Residential Sprinklers



Residential Sprinklers							
Model	SIN Number	Orientation	Thread size	K-Factor	Operating element	Specifications	Data Sheet
LFII	TY1234	Pendent	1/2"	K-(3.0) IMP	3 mm Bulb	Wet Pipe Systems	TFP402
LFII	TY2234	Pendent	1/2"	K-(4.9) IMP	3 mm Bulb	Wet Pipe and Dry Pipe Systems	TFP400
LFII	TY2236	Pendent	1/2"	K-(4.9) IMP	3 mm Bulb	Wet Pipe Systems	TFP403
LFII	TY3934	Pendent	1/2"	K-(4.9) IMP	3 mm Bulb	Recessed Pendent Wet Pipe Systems	TFP401
LFII	TY4234	Pendent/ Concealed	3/4"	K-(6.9) IMP	3 mm Bulb	NFPA 13 Optimized Wet Pipe Systems	TFP408
LFII	TY1334	Horizontal Sidewall	1/2"	K-(4.2) IMP	3 mm Bulb	Wet Pipe and Dry Pipe Systems	TFP410
LFII	TY2334	Horizontal Sidewall	1/2"	K-(4.4) IMP	3 mm Bulb	Wet Pipe Systems	TFP412
LFII	TY3334	Horizontal Sidewall	1/2"	K-(5.6) IMP	3 mm Bulb	NFPA 13 Optimized Wet Pipe Systems	TFP415
LFII	TY4334	Horizontal Sidewall	1/2"	K-(5.8) IMP	3 mm Bulb	NFPA 13 Optimized Wet Pipe Systems	TFP417
LFII	TY2234	DP Concealed Pendent	1/2"	K-(4.9) IMP	3 mm Bulb	Wet Pipe and Dry Pipe Systems	TFP450
LFII	TY2324	Concealed H-Sidewall	1/2"	K-(4.2) IMP	Solder	Wet Pipe Systems	TFP445
LFII	TY2534	Concealed Pendent	1/2"	K-(4.9) IMP	Glass Bulb	Flat Plate, Wet Pipe System	TFP446
LFII	TY3584	Concealed Pendent	1/2"	K-(5.8) IMP	Glass Bulb	Flat Plate, Wet Pipe System	TFP448
LFII	TY2235	Recessed Pendent	1"	K-(4.9) IMP	3 mm Bulb	Dry Type Wet Pipe and Dry Pipe Systems	TFP460
LFII	TY2335	Horizontal Sidewall,	1"	K-(4.4) IMP	3 mm Bulb	Dry Type Wet Pipe System	TFP461

Residential Sprinklers

FAST RESPONSE

tyco

LFII, 3mm Glass Bulb Type, 1/2" NPT (15mm) Pendent

K-Factor (3.0) IMP - Wet Pipe Systems, Fast Response

SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY1234	Pendent	1/2" NPT 15mm	K-(3) IMP	Natural Brass	68°C/155°F	51-010-1-155
				Chrome		51-010-9-155
				Signal White	79°C/175°F	51-010-4-155
				Natural Brass		51-010-1-175
				Chrome		51-010-9-175
				Signal White		51-010-4-175



K-Factor (4.9) IMP - Wet Pipe and Dry Pipe Systems, Fast Response

SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY2234	Pendent	1/2" NPT 15mm	K-(4.9) IMP K-(7.1) MET	Natural Brass	68°C/155°F	51-201-1-155
				Chrome		51-201-9-155
				Signal White	79°C/175°F	51-201-4-155
				Pure White		51-201-3-155
				Natural Brass		51-201-1-175
				Chrome		51-201-9-175
				Signal White		51-201-4-175
				Pure White		51-201-3-175



K-Factor (4.9) IMP - Wet Pipe Systems, Fast Response

SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY2236	Pendent	1/2" NPT 15mm	K-(4.9) IMP K-(7.1) MET	Natural Brass	68°C/155°F	51-212-1-155
				Chrome		51-212-9-155
				Signal White	79°C/175°F	51-212-4-155
				Pure White		51-212-3-155
				Jet Black		51-212-5-155
				Natural Brass		51-212-1-175
				Chrome		51-212-9-175
				Signal White		51-212-4-175
				Jet Black		51-212-5-175



K-Factor (5.8) IMP - Wet Pipe Systems, Fast Response

SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY3934	Pendent	1/2" NPT 15mm	K-(5.8) IMP	Natural Brass	68°C/155°F	51-058-1-155
				Chrome		51-058-9-155
				Signal White	79°C/175°F	51-058-4-155
				Pure White		51-058-3-155
				Jet Black		51-058-5-155
				Natural Brass		51-058-1-175
				Chrome		51-058-9-175
				Signal White		51-058-4-175
				Pure White		51-058-3-175



DataSheet
TFP402



DataSheet
TFP400



DataSheet
TFP403



DataSheet
TFP401

▲
Back to Table
of Contents



Residential Sprinklers

FAST RESPONSE

tyco

LFII, 3mm Glass Bulb Type, 3/4" NPT (20mm)

Pendent/Recessed Pendent/Concealed

K-Factor (6.9) IMP – NFPA 13 Optimized Wet Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP – °C /°F	PART NUMBER
TY4234	Pendent	3/4" NPT 20mm	K-(6.9) IMP	Natural Brass Chrome Signal White Pure White	68°C/155°F	51-069-1-155 51-069-9-155 51-069-4-155 51-069-3-155
				Natural Brass Chrome Signal White Pure White	79°C/175°F	51-069-1-175 51-069-9-175 51-069-4-175 51-069-3-175
Concealed Pendent Sprinkler Assembly without Cover Plate Assembly				68°C/155°F		51-068-1-155
Cover Plate Assembly				Chrome Pure White (RAL 9010) Signal White (RAL 9003) Custom Paint		56-873-9-135 56-873-3-135 56-873-4-135 56-873-X-135
Recessed Escutcheon				Separately Order		



DataSheet
IFP408

Back to Table
of Contents



Residential Sprinklers

FAST RESPONSE

tyco

LFII, 3mm Glass Bulb Type, 1/2" NPT (15mm) Horizontal Sidewall

K-Factor (4.2) IMP - Wet Pipe and Dry Pipe Systems, Fast Response						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY1334	Horizontal Sidewall	1/2" NPT 15mm	K-(4.2) IMP	Natural Brass	68°C/155°F	51-211-1-155
				Chrome		51-211-9-155
				Signal White		51-211-4-155
				Pure White		51-211-3-155
				Jet Black		51-211-5-155
				Natural Brass	79°C/175°F	51-211-1-175
				Chrome		51-211-9-175
				Signal White		51-211-4-175
				Pure White		51-211-3-175
				Jet Black		51-211-5-175



K-Factor (4.4) IMP - Wet Pipe Systems, Fast Response						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY2334	Horizontal Sidewall	1/2" NPT 15mm	K-(4.4) IMP	Natural Brass	68°C/155°F	51-215-1-155
				Chrome		51-215-9-155
				Signal White		51-215-4-155
				Jet Black		51-215-5-155
				Natural Brass	79°C/175°F	51-215-1-175
				Chrome		51-215-9-175
				Signal White		51-215-4-175
				Pure White		51-215-5-175



K-Factor (5.6) IMP - NFPA 13 Optimized Wet Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY3334	Horizontal Sidewall	1/2" NPT 15mm	K-(5.6) IMP	Natural Brass	68°C/155°F	51-524-1-155
				Chrome		51-524-9-155
				Signal White		51-524-4-155
				Jet Black		51-524-3-155
				Natural Brass	79°C/175°F	51-524-1-175
				Chrome		51-524-9-175
				Signal White		51-524-4-175
				Pure White		51-524-3-175



K-Factor (5.8) IMP - NFPA 13 Optimized Wet Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY4334	Horizontal Sidewall	1/2" NPT 15mm	K-(5.8) IMP	Natural Brass	68°C/155°F	51-534-1-155
				Chrome		51-534-9-155
				Signal White		51-534-4-155
				Natural Brass	79°C/175°F	51-534-1-175
				Chrome		51-534-9-175
				Signal White		51-534-4-175



DataSheet
TFP410

Back to Table
of Contents



DataSheet
TFP412



DataSheet
TFP415



DataSheet
TFP417



Residential Sprinklers

FAST RESPONSE

tyco

LFII, 3mm Glass Bulb Type, 1/2" NPT (15mm)

Domed-Plate Concealed Pendent

K-Factor (6.9) IMP - NFPA 13 Optimized Wet Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY2234	Domed-Plate Concealed Pendent	1/2" NPT 15mm	K-(4.9) IMP	Brass	68°C/155°F	51-873-1-155
Cover Plate Assembly				Chrome Pure White (RAL 9010) Signal White (RAL 9003) Custom Paint		56-873-9-135 56-873-3-135 56-873-4-135 56-873-X-135



LFII, Solder, 1/2" NPT (15mm)

Concealed Horizontal Sidewall

K-Factor (6.9) IMP – NFPA 13 Optimized Wet Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP – °C /°F	PART NUMBER
TY2324	Concealed Horizontal Sidewall	1/2" NPT 15mm	K-(4.2) IMP	Brass	71°C/160°F	50-520-1-160
Cover Plate Assembly				Ivory (RAL1015)	56-204-0-135	
				Beige (RAL1001)	56-204-2-135	
				Pure White (RAL9010)	56-204-3-135	
				Signal White (RAL9003)	56-204-4-135	
				Gray White (RAL9002)	56-204-5-135	
				Brown (RAL8028)	56-204-6-135	
				Black (RAL9005)	56-204-7-135	
				Brushed Brass	56-204-8-135	
				Brushed Chrome	56-204-9-135	
				Custom Paint	56-204-X-135	



DataSheet
ITP450

▲
Back to Table
of Contents



DataSheet
ITP445



Residential Sprinklers

FAST RESPONSE



LFII, Glass Bulb Type, 4.9 K-factor, 1/2" NPT (15mm) Concealed Pendent Sprinkler

K-Factor (4.9) IMP - Flat Plate, Wet Pipe System						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY2534	Concealed Pendent Sprinkler	1/2" NPT 15mm	K-(4.9) IMP	Brass	68°C/155°F 93°C/200°F	51-549-1-155 51-549-1-200
Cover Plate Assembly			Ivory (RAL1015) Bright Chrome Beige (RAL1001) Pure White (RAL9010) Signal White (RAL9003) Gray White (RAL9002) Brown (RAL8028) Black (RAL9005) Brushed Brass Brushed Chrome Custom Paint		59°C/139°F	56-891-0-135 56-891-9-135B 56-891-2-135 56-891-3-135 56-891-4-135 56-891-5-135 56-891-6-135 56-891-7-135 56-891-8-135 56-891-9-135 56-891-X-135
			Ivory (RAL1015) Bright Chrome Beige (RAL1001) Pure White (RAL9010) Signal White (RAL9003) Gray White (RAL9002) Brown (RAL8028) Black (RAL9005) Brushed Brass Brushed Chrome Custom Paint		75°C/165°F	56-891-0-165 56-891-9-165B 56-891-2-165 56-891-3-165 56-891-4-165 56-891-5-165 56-891-6-165 56-891-7-165 56-891-8-165 56-891-9-165 56-891-X-165



DataSheet
TFP446

▲
Back to Table
of Contents



Residential Sprinklers

FAST RESPONSE

tyco

LFII, Glass Bulb Type, 5.8 K-factor, 1/2" NPT (15mm) Concealed Pendent Sprinkler

K-Factor (5.8) IMP - Flat Plate, Wet Pipe System						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH	TEMP - °C /°F	PART NUMBER
TY3584	Concealed Pendent Sprinkler	1/2" NPT 15mm	K-(5.8) IMP	Brass	68°C/155°F 93°C/200°F	51-558-1-155 51-558-1-200
Cover Plate Assembly			Ivory (RAL1015) Bright Chrome Beige (RAL1001) Pure White (RAL9010) Signal White (RAL9003) Gray White (RAL9002) Brown (RAL8028) Black (RAL9005) Brushed Brass Brushed Chrome Custom Paint		59°C/139°F	56-891-0-135 56-891-9-135B 56-891-2-135 56-891-3-135 56-891-4-135 56-891-5-135 56-891-6-135 56-891-7-135 56-891-8-135 56-891-9-135 56-891-X-135
			Ivory (RAL1015) Bright Chrome Beige (RAL1001) Pure White (RAL9010) Signal White (RAL9003) Gray White (RAL9002) Brown (RAL8028) Black (RAL9005) Brushed Brass Brushed Chrome Custom Paint		75°C/165°F	56-891-0-165 56-891-9-165B 56-891-2-165 56-891-3-165 56-891-4-165 56-891-5-165 56-891-6-165 56-891-7-165 56-891-8-165 56-891-9-165 56-891-X-165



DataSheet
IFP448

▲
Back to Table
of Contents



Residential Sprinklers

FAST RESPONSE



LFII, K-FACTOR (4.9) IMP, 3mm Glass Bulb Type Recessed Pendent

K-Factor (4.9) IMP – Dry Type Wet Pipe and Dry Pipe Systems						
SIN NUMBER	ORIENTATION	THREAD SIZE	K-FACTOR	FINISH		TEMP – °C /°F
TY2235	Pendent With Recessed Escutcheon	1" NPT 25mm	K-(4.9) IMP	SPRINKLER	ESCUTCHEON	68°C/155°F 68°C/155°F
		ISO 7-R		Natural Brass Signal White Chrome	Natural Brass Signal White Chrome	



PART NUMBER: *-63-10X-X-XXX

X	TEMPERATURE RATING
1	68°C/155°F
2	68°C/155°F**

X	SPRINKLER FINISH	ESCUTCHEON FINISH
2	Natural Brass	Brass Plated
4	Signal White (RAL9003)	Signal White (RAL9003)
9	Chrome Plated	Chrome Plated

XXX	ORDER LENGTH (EXAMPLES)
055	5.50 in.
082	8.25 in.
180	18.00 in.
187	18.75 in.
240	24.00 in.

Notes:

* Use Prefix "I" for ISO 7-R 1 Inlet Thread Connection (e.g., I-63-101-9-180)

** (68°C/155°F) Wet pipe system only



DataSheet
TFP460

Back to Table
of Contents





Fire Factory Australia is an active distributor of TYCO Fire Protection Products.

For ordering and enquiries, please [contact](#) our team.

For the latest information on product specifications, certifications, approvals, and technical details, always refer to the Tyco product datasheets.

Our experienced team is available to assist you in selecting the most suitable sprinkler for your project and to provide professional, project-specific advice.

Fire Factory Australia

Unit 2/2 Parramatta Rd, Granville NSW 2142, Australia

P: (02)9756 0087

E: sales@firefactory.com.au

W: www.firefactory.com.au

Product specifications, approvals, and availability are subject to change without notice. Always refer to the latest Tyco Fire Protection Products datasheets for complete and current information.