



Quick and easy installation

4W LED Wide Body EXIT Light

Approved to Australian Standard AS2293.3

EX50LED

4W LED Wall Mounted EXIT Light



EX50LED-1

4W LED Ceiling Mounted EXIT Light



Specifications

- Power Supply: 220-240V 50/60Hz
- Charge Time: 24 Hours
- Discharge Time: 2 Hours
- Battery: Li-FePO4 3.2V 3000mAh
- LED Lamp: 40pcs
- Colour Temperature: 6000k
- Dimension (L x W x H): 380mm x 110mm x 160mm

Specifications

- Power Supply: 220-240V 50/60Hz
- Charge Time: 24 Hours
- Discharge Time: 2 Hours
- Battery: Li-FePO4 3.2V 3000mAh
- LED Lamp: 40pcs
- Colour Temperature: 6000k
- Dimension (L x W x H): 380mm x 160mm x 225mm

The new Fire Factory Au Technology LED Exit light delivers the advantage of LED technology in surface mount ceiling or wall luminaries. The LED light sources used are up to 75% more energy efficient compares to the traditional light sources. Using LED allows quick and easy installation, Environmental friendly. LED delivers longer life than the conventional light average life of 50000 hours and most of all it is easier to install.

Product Features

- Quick and easy installation
- Suits 24M viewing distances
- Quick connect bracket for fast wall / ceiling mounting
- Energy Saving
- Environmental friendly
- Low wattage, low energy consumption
- Average 50000 hours LED Lamp life
- Maintained or Non-Maintained operation mode
- Test Button
- 5 Years Warranty *** Excluding Battery
- Approved with Australian Standard AS2293.3



Operational Information – EX50LED Ceiling Mounted

General				Battery	
Voltage (V)	220-240v	Viewing Distance	24m	Battery Type	Li-FePO4
Frequency (Hz)	50/60 Hz	Classification	C0:E5, C90:E4	Battery Code	3.2V 3000mAh
Max Ambient Temp.	25 ~ + 50°C	Mounting Type	Wall Mounted	Duration	2 hours
Class	Class 1	IP Rating	IP20	Charging Time	24 hours
Wiring	Terminal 10mm	Colour temp	6000k	Charger Operation	Continuous
Luminous Flux	360lm	Ra	≥75		

Operational Information – EX50LED-1 Ceiling Mounted

General				Battery	
Voltage (V)	220-240v	Viewing Distance	24m	Battery Type	Li-FePO4
Frequency (Hz)	50/60 Hz	Classification	C0:E20, C90:E16	Battery Code	3.2V 3000mAh
Max Ambient Temp.	25 ~ + 50°C	Mounting Type	Ceiling Mounted	Duration	2 hours
Class	Class 1	IP Rating	IP45	Charging Time	24 hours
Wiring	Terminal 10mm	Colour temp	6000k	Charger Operation	Continuous
Luminous Flux	360lm	Ra	≥75		

