



FIRE EQUIPMENT PRODUCTS
100% Australian owned

FFA-SALED Smart Adjustable LED 2 foot & 4 foot Twin Emergency Batten

Remote control is optional



FFA-SALED25-2F-ES:16W/20W/25W FFA-SALED36-4F-ES:25W/30W/36W



IP65

LM79

LM80

Operational Information - FFA-TPLED25-2F-ES Smart LED Tri-proof 2 foot Twin Emergency Batten with CCT

General				Battery	
Voltage (V)	220-240v	Viewing Distance	N/A	Battery Type	Li-ion
Frequency (Hz)	50/60 Hz	Classification	C:0=D100 C:90=D50	Battery Code	18650 - Li-FePO4 6.4V 2Ah 12.8Wh
Max Ambient Temp.	25~+50°C	Mounting Type	Ceiling / Wall Mounted	Duration	3 hours
Class	Class 1	IP Rating	IP20	Charging Time	24 hours
Colour temp	4000k, 5000k, 6000k	Ra	≥80	Charger Operation	Continuous

Operational Information - FFA-TPLED36-4F-ES Smart LED Tri-proof 4 foot Twin Emergency Batten with CCT

General				Battery	
Voltage (V)	220-240v	Viewing Distance	N/A	Battery Type	Li-ion
Frequency (Hz)	50/60 Hz	Classification	C:0=D100 C:90=D50	Battery Code	18650 - Li-FePO4 6.4V 3Ah 19.2Wh
Max Ambient Temp.	25~+50°C	Mounting Type	Ceiling / Wall Mounted	Duration	3 hours
Class	Class 1	IP Rating	IP20	Charging Time	24 hours
Colour temp	4000k, 5000k, 6000k	Ra	≥80	Charger Operation	Continuous

Product Features:

1. Product Width : 125mm, Length: 600mm, 1200mm for option.
2. CCT selectable: 4000K/5000K/6000K.
3. Power Selectable: FFA-SALED25-2F-ES: 16W/20W/25W, FFA-SAL ED36-4F-ES: 25W/30W/36W
4. Complete certifications, all models cover SAA certification and AS2293.3 certification.
5. The light source part is separated from the lamp body part. Prevent mosquitoes from entering the light source part.
6. The light is very even and there is no dark area in the middle of the lamp.
7. All with dimming driver, and the sensing mode can be adjusted according to customer needs. (After people leave, how long it takes for the brightness to change can be freely set. And in the sensor mode, lamp can be completely turn